MATERIAL SAFETY DATA SHEET

PRODUCT NAME: PRE-MIXED CONCRETE PATCH HMIS CODES: H F R P
PRODUCT CODE: 2043 0 0 0

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Custom Building Products, Inc.
ADDRESS: 6511 SALT LAKE AVE., BELL, CA. 90201
EMERGENCY PHONE: (213) 582-0846 INFORMATION PHONE: (213) 582-0846
DATE REVISED : 04-13-94 NAME OF PREPARER : STEVE TAYLOR
REASON REVISED : ADDITIONAL INFORMATION: HEALTH SECTION VI.

SECTION II - INGREDIENTS/SARA III INFORMATION

COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS OSHA PEL	ACGIH TLV	VAPOR PRESSURE mm Hg @ TEMP	Wt. %
CALCIUM CARBONATE/ LIMESTONE	1317-65-3	10mg/M3		N/A	25
ETHYLENE GLYCOL	107-21-1	50 PPM		0.1 68F	0.92
SILICON DIOXIDE; SILICA, CRYSTALLINE	14808-60-7	10mg/M3	.3mg/M3	N/A	40

* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: 100C SPECIFIC GRAVITY (H2O=1): 1.8
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
SOLUBILITY IN WATER: DISPERSIBLE
APPEARANCE AND ODOR: SANDY GRAY MORTAR/MASTIC/SLIGHT ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES
NONE

UNUSUAL FIRE AND EXPLOSION HAZARDS
CONTAINERS MAY RUPTURE IF EXPOSED TO EXTREME TEMPERATURES.
MATERIAL MAY SPATTER ABOVE 212F.

SECTION V - REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID
EXTREME TEMPERATURES.

INCOMPATIBILITY (MATERIALS TO AVOID)
STRONG ACIDS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
THERMAL DECOMPOSITION WILL YIELD CARBON MONOXIDE AND CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
SKIN CONTACT: IRRITATING TO SKIN UPON REPEATED OR PROLONGED CONTACT.
EYE CONTACT: MAY CAUSE SLIGHT TRANSIENT (TEMPORARY) EYE IRRITATION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
REPEATED SKIN EXPOSURE TO LARGE QUANTITIES MAY RESULT IN ABSORPTION OF HARMFUL AMOUNTS. THE DERMAL LD50 HAS NOT BEEN DETERMINED.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
MAY CAUSE GASTROINTESTIONAL IRRITATION.

HEALTH HAZARDS (ACUTE AND CHRONIC)
ACUTE: PRE-EXISTING SKIN, EYE, AND RESPIRATORY CONDITIONS MAY BE AGGRAVATED BY EXPOSURE.
CHRONIC: NONE

CARCINOGENICITY: NTP? YES IARC MONOGRAPHS? YES OSHA REGULATED? YES THERE IS SUFFICIENT EVIDENCE FOR THE CARCINOGENICITY OF CRYSTALLINE SILICA TO EXPERIMENTAL ANIMALS, AND THAT THERE IS LIMITED EVIDENCE OF THE CARCINOGENICITY OF CRYSTALLINE SILICA TO HUMANS.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
NONE KNOWN.

EMERGENCY AND FIRST AID PROCEDURES
EYE CONTACT: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. SEE PHYSICIAN IF IRRITATION RESULTS.
SKIN CONTACT: WASH WITH WATER. SEEK MEDICAL ATTENTION IF IRRITATION RESULTS.
INHALATION: IF AFFECTED, REMOVE TO FRESH AIR.
INGESTION: IF SWALLOWED, IMMEDIATELY INDUCE VOMITING BY GIVING TWO GLASSES OF WATER AND STICKING FINGER DOWN THROAT. CALL A PHYSICIAN. NEVER GIVE ANYTHING BY MOUTH OR ATTEMPT TO INDUCE VOMITING TO AN UNCONSCIOUS PERSON.

========== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE ==========

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
AVOID ENTRY INTO SEWERS OR NATURAL WATER WAYS. SMALL SPILLS: SOAK UP WITH ABSORBANT MATERIALS. LARGE SPILLS: DIKE AND PUMP INTO SUITABLE CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL METHOD
DISPOSE OF PRODUCT IN ACCORDANCE WITH APPLICABLE LOCAL, COUNTY, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
STORE IN COOL, DRY AREA OUT OF SUNLIGHT. STORE AWAY FROM HEAT OR ANY OTHER SOURCES OF HEAT. PROTECT FROM FREEZING.

OTHER PRECAUTIONS
NONE

========== SECTION VIII - CONTROL MEASURES ==========

RESPIRATORY PROTECTION
EXPOSURE MAY EXCEED TLV RANGE. USE A NIOSH APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE.

VENTILATION
GENERAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP VAPOR CONCENTRATIONS WITHIN SPECIFIED TLV RANGES.

PROTECTIVE GLOVES
THE USE OF PLASTIC OR RUBBER GLOVES IS ADVISED TO PREVENT SKIN IRRITATION TO SENSITIVE INDIVIDUALS.

EYE PROTECTION
SAFETY GLASSES ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT
ADEQUATE CLOTHING SHOULD BE WORN TO PREVENT SKIN CONTACT.

WORK/HYGIENIC PRACTICES
GOOD HOUSEKEEPING PRECEDURES SHOULD BE PRACTICED.

========== SECTION IX - DISCLAIMER ==========

DISCLAIMER
THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.